

Technical Data Sheet

Updated: 1/2/2015

HOT SHOT'S SECRET DIESEL EXTREME Clean and Boost

Product Overview

Diesel Extreme cleans everything in your diesel's fuel system, removing dirt and water that reduce power and performance. It is the most concentrated fuel additive available.

Applications and Uses

Diesel Extreme is safe in all diesel engines: semi-trucks, pick-up trucks, farm and construction equipment, autos, mowers, buses, RVs, and motor homes. These include but are not limited to Ford Powerstroke, Dodge Cummins, GM Duramax, Saab, Volkswagen, and Audi.

For maximum performance, use Diesel Extreme on the fuel side in combination with Hot Shot's Secret Stiction Eliminator on the oil side.

Benefits

- Cleans fuel tank, lines, and injectors
- Removes internal diesel injector deposits (IDIDs)
- Removes free water from the system
- Stabilizes fuel

- Boosts cetane by 5-6 points
- Neutralizes acid
- Lubricates the fuel pump and injectors
- Inhibits rust and corrosion in tank and lines

Diesel Extreme upgrades power and performance, resulting in quicker response, improved mileage, better cold starts, and reduced maintenance.

Directions for Use

Use Diesel Extreme only once every 6 months. At fuel fill-up, add:

| Diesel Fuel | Hot Shot's Secret Diesel Extreme |
|---------------|----------------------------------|
| 30-40 gallons | 16 ounces (1/2 quart) |
| 75 gallons | 1 quart |
| 150 gallons | 2 quarts |

CAUTION: Use only in diesel fuel.

Lubrication Specialties, Inc.

255 Neal Ave. | Mt. Gilead, OH 43338

Phone: 1-800-341-6516 | Fax: 415-946-3554 | Email: Info@lubricationspecialties.com | www.HotShotsSecret.com



Packaging

Diesel Extreme is available in:

- 16 ounce bottle (1/2 quart)
- 2 quart bottle (1/2 gallon)

• 1 quart bottle

• 5 gallon bucket

Typical Properties

| Property or Test | Result |
|-----------------------------|-----------|
| API gravity @ 60 °F | 26.9 |
| Viscosity @ 100 °F, SUS | 43 |
| Viscosity @ 100 °F, CS | 5.2 |
| Flash point, °F | 102 |
| Pour point, °F | -60 |
| Acid test | Excellent |
| Ash content | None |
| Copper strip corrosion test | Pass |
| Gum and varnish test | Excellent |
| Storage stability | Excellent |

The Safety Data Sheet is available at

http://www.hotshotsecret.com/print-documents/.



255 Neal Ave. | Mt. Gilead, OH 43338

Phone: 1-800-341-6516 | Fax: 415-946-3554 | Email: Info@lubricationspecialties.com | www.HotShotsSecret.com